VERMEER ULTRA X3 DRILLING SYSTEM

Unique, non-torque spline connection system for quick tooling switches



Key features:

- Provides the ability to swap out tooling quickly without the use of specialty tooling or breakout devices
- Features standard API rear connection, which will also work with quickconnect systems
- Can ream directly from the transmitter housing
- Eliminates the need for starter rods and adapters in certain application and ground conditions

For more information about the Vermeer Ultra X3 drilling system, contact your local Vermeer dealer and visit borestore.com.

Available in three sizes for drilling rigs up to a 40,000-pound (177.9-kN) drill range

Versatile compatibility

- Gauntlet bit
- I ance Pro bit
- Single roller-cone bits
- And more plate bits and rock tooling

Construction material

• Manufactured with durable, high-alloy material

Size options

- Ultra X3 375 for horizontal directional drills (HDDs) in the 40,000-pound (177.9-kN) drill range — Vermeer D40x55 S3 or Ditch Witch JT40 HDD
- Ultra X3 325 for HDDs in the 24,000-pound (106.8-kN) drill range — Vermeer D23x30 S3, Vermeer D24x40 S3 or Ditch Witch JT30 HDD
- Ultra X3 275 for HDDs in the 10,000-pound (44.5-kN) drill range — Vermeer D10x15 S3 or Ditch Witch JT10 HDD

BORESTORE HDD TOOLING AND ACCESSORIES WAREHOUSE

borestore.com

Vermeer



Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown i for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications.